

# HIP



## สัญญาณภาพคมชัด ปลอดภัยทุกพื้นที่ 2MP VF Bullet Network Camera



กันน้ำระดับ IP 67

MODEL  
**CMU1292**

ตอบโจทย์ CCTV HIP คุณภาพ  
ภาพคมชัดระดับ Full HD

**2.0**  
MegaPixel

Full HD  
CAMERA



Office



Data Room



Apartment



Hotel



Custom



Sky Walk



Villa



Bank



2MP



Ultra  
H.265



WDR



Built-in Mic



Edge  
Storage



Corridor  
Mode



POE



IP 67

### FEATURES

- ▶ High quality image with 2MP, 1/2.7" CMOS sensor
- ▶ 2MP (1920\*1080)@30/25fps; 720P (1280\*720)@30/25fps
- ▶ Ultra 265, H.265, H.264
- ▶ 120dB true WDR technology enables clear image in strong light scene
- ▶ Support 9:16 Corridor Mode
- ▶ Built-in Mic
- ▶ Smart IR, up to 50m (164ft) IR distance
- ▶ Supports 128 G Micro SD card
- ▶ IP67 protection
- ▶ Support PoE power supply
- ▶ 3-Axis

ISO9001:2015

ขอสงวนสิทธิ์ในการเปลี่ยนแปลงรายละเอียดโดยไม่ต้องแจ้งให้ทราบล่วงหน้า บริษัท เอช ไอ พี โกลบอล จำกัด

THE BEST  
SECURITY SOLUTION



# 2MP VF Bullet Network Camera CMU1292



# HIP



ใช้งานร่วมกับ Network video Record

## Technical Specifications

Model	CMU1292
<b>Camera</b>	
Sensor	1/2.7", 2.0 megapixel, progressive scan, CMOS Colour: 0.005Lux (F1.6, AGC ON)
Minimum Illumination	0Lux with IR on
Day/Night	IR-cut filter with auto switch (ICR)
Shutter	Auto/Manual, 1 ~ 1/100000s
S/N	>52dB
WDR	120dB
<b>Lens</b>	
Lens Type	2.8 ~ 12mm, AF automatic focusing and motorized zoom lens
Lens Mount	Φ14
Angle of View (H)	108.05°~ 32.59°
Angle of View (V)	56.81°~ 18.36°
<b>Illuminator</b>	
IR Range	Up to 50m (164ft) IR range
IR On/Off Control	Auto/Manual
<b>Video</b>	
Video Compression	Ultra 265, H.265, H.264
Resolution	Main Stream: 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps; Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360, Max 30fps;
Video Bit Rate	128 Kbps~6144 kbps
Support	Motion Detection , Privacy Mask
<b>Image</b>	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Image Setting	Image rotation, brightness, saturation, contrast, sharpness, gain adjustable by web browser
Digital noise reduction	2D/3D DNRS
Smart IR	supported
Flip	Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise
HLC	Supported
BLC	Supported
Defog	Digital Defog
<b>Audio</b>	
Audio Compression	G.711
Suppression	Supported
Sampling Rate	8KHZ
<b>Storage</b>	
Edge Storage	Micro SD, up to 128GB
Network Storage	ANR, NAS(NFS)
<b>Network</b>	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL/TLS, QoS, SNMP, ONVIF
User/Host	Up to 32 users. 2 user levels: administrator and common user
Security	Password protection, Strong password, HTTPS encryption, Export operation logs, Basic and digest authentication for RTSP, Digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+
<b>Interface</b>	
Network	10/100M Base-TX Ethernet
Built-in Mic	Supported
<b>General</b>	
Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 8.5W
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Ingress Protection	IP67