

# HIP

## Key Tag

### Specifications

Chip	TK28 , TK4100
Operating Frequency	125 kHz (*Option Mifare 13.56MHz)
Material	ABS / PU (ตามรุ่น)
Operating Temperature	-25°C~55°C
Storage temperature	-25°C~50°C



**HL-1**  
Yellow & Blue

วัสดุ: ABS  
ขนาด: 43.7\*30.5\*5.3 mm



**HL-3**  
Yellow & Blue

วัสดุ: ABS  
ขนาด: 40.5\*32\*4.2 mm



**HL-2**

วัสดุ: ABS  
ขนาด: 35.3\*28\*6.4mm



**HL-4**

วัสดุ: ABS  
ขนาด: 46\*28\*5mm



**HL-5**

วัสดุ: ABS  
ขนาด: 53\*37.5\*9.8mm



**HL-6**

วัสดุ: ABS  
ขนาด: 52.5\*35.2\*9mm



**HL-7**

วัสดุ: ABS  
ขนาด: 55.8\*37.3\*8.8mm



**HL-8**

วัสดุ: ABS  
ขนาด: 51.4\*32.3\*5.6mm



**HL-9**

วัสดุ: ABS  
ขนาด: 34.8\*23\*3.9mm



**HL-10**

Transparent  
วัสดุ: ABS  
ขนาด: 55.5\*35.5\*7mm



**HL-11**

วัสดุ: ABS  
ขนาด: 55\*37.5\*6.9mm



**HL-12**

วัสดุ: ABS  
ขนาด: 51\*40\*9mm



**HL-13**

วัสดุ: ABS  
ขนาด: 51\*38\*8.8mm



**HL-14**

วัสดุ: ABS  
ขนาด: 39\*39\*5mm



**HL-15**

วัสดุ: ABS  
ขนาด: 53.9\*33.8\*5mm



**HL-16**

วัสดุ: ABS  
ขนาด: 37.5\*31\*5.5mm



**HL-PU1**

วัสดุ: หนัง  
ขนาด: 51.2\*51.2\*6.5mm



**HL-PU2**

วัสดุ: หนัง  
ขนาด: 48\*36.2\*6.5mm



**HL-PU3**

วัสดุ: หนัง  
ขนาด: 56\*36\*6.5mm



**HL-PU4**

วัสดุ: หนัง  
ขนาด: 39\*39\*5.5mm



**HL-PU5**

วัสดุ: หนัง  
ขนาด: 33\*48\*4.5mm