

# HIP

## NETWORK VIDEO RECORD 32-Channel



4K / 5MP / 4MP / 3MP / 1080P / HD NVR

MODEL  
CMU3132-H2

ตอบโจทย์เครื่องบันทึก 32 Channel  
ภาพคมชัดระดับ 4K



ULTRA  
H.265



### FEATURES

- ▶ Support Ultra265/H.265/H.264 video formats
- ▶ 32-channel input
- ▶ Third-party IP cameras supported with ONVIF conformance : Profile S, Profile G, Profile T
- ▶ HDMI and VGA simultaneous output
- ▶ Up to 8 Megapixels resolution recording
- ▶ Accurate retrieval, instant playback
- ▶ 2 SATA HDDs, up to 10TB for each HDD
- ▶ ANR technology to enhance the storage reliability when the network is disconnected
- ▶ Support cloud upgrade

ISO9001:2015

ขอสงวนสิทธิ์ในการเปลี่ยนแปลงรายละเอียดโดยไม่ต้องแจ้งให้ทราบล่วงหน้า บริษัท เอช ไอ พี โกลบอล จำกัด

THE BEST  
SECURITY SOLUTION





**NETWORK VIDEO RECORD**  
**32-Channel**  
**Model : CMU3132-H2**



**ULTRA  
H.265**



# Specifications

<b>Model</b>	<b>NVR CMU3132-H2</b>
<b>Video/Audio Input</b>	
IP Video Input	32-ch
Two-way Audio Input	1-ch, RCA
<b>Network</b>	
Incoming bandwidth	160Mbps
Outgoing bandwidth	64Mbps
Remote Users	128
Protocols	P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, SMTP, NTP, SNMP, RTSP, IPv4, IPv6, ONVIF
<b>Video/Audio Output</b>	
HDMI/VGA Output	HDMI: 4K (3840x2160) @30, 1920x1080p@60, 1920x1080p@50, 1600x1200@60, 1280x1024@60, 1280x720@60, 1024x768@60 VGA: 1920x1080p@60, 1920x1080p@50, 1280x1024@60, 1280x720@60, 1024x768@60
Audio Output	1-ch, RCA
Recording Resolution	8MP/5MP/4MP/3MP/1080p/960p/720p/960H/D1/2CIF/CIF
Synchronous Playback	4-ch
Corridor Mode Screen	3/4/5/7/9/10/12/16/32
<b>Decoding</b>	
Decoding format	Ultra265/H.265/H.264
Live view/ Playback	8MP/5MP/4MP/3MP/1080p/960p/960H/720p/D1/2CIF/CIF
Capability	2 x 4K@30, 3 x 5MP@30, 4 x 4MP@30, 5 x 3MP@30, 8 x 1080p@30, 16 x 720p@30
<b>Hard Disk</b>	
SATA	2 SATA interfaces
Capacity	up to 10TB for each disk (environment temperature should be below 30°C)
<b>Smart</b>	
VCA Detection	Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking
VCA Search	Face search, Behavior search
Statistical Analysis	People counting
<b>External Interface</b>	
Network Interface	1 RJ-45 10M/100M/1000M self-adaptive Ethernet Interfaces
USB Interface	Rear panel: USB x 2
<b>General</b>	
Power Supply	12V DC Power Consumption: ≤ 15W( without HDD )
Working Environment	-10°C ~ + 55°C (+14°F ~ +131°F), Humidity ≤ 90% RH(non-condensing)
Dimensions (WxDxH)	380mm × 318mm ×45mm
Weight (without HDD)	≤ 3.15 Kg (6.94 lb)

**ISO9001:2015**

Copyright © HIP GLOBAL All Rights Reserved.



HIPGLOBAL



@HIPGROUP



HIP Channel



@HIPGLOBAL



www.hip.co.th

**THE BEST  
SECURITY SOLUTION**

