

HIP




2.0
MegaPixel

Full HD
CAMERA

Model:
CMU1202
2MP Bullet
Network Camera (2.8mm)



Water Proof IP 67



Office

Data Room

Apartment

Hotel

Cashbox Management

Custom

Villa

Bank

FEATURES

- High quality image with 2MP, 1/2.8"CMOS sensor
- 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
- Ultra 265, H.265, H.264
- Smart IR, up to 30m (98ft) IR distance
- Day/night functionality
- 2D/3D DNR (Digital Noise Reduction)
- IP67 protection
- Support PoE power supply
- 3-Axis

2MP

Ultra H.265

POE

WDR

Smart IR

HLC

Smart Search



ISO9001:2015

Copyright © HIP GLOBAL All Rights Reserved.



HIPGROUP



@HIPGROUP



HIP CHANNEL



www.hip.co.th

THE BEST
SECURITY SOLUTION



2MP Bullet Network Camera (2.8mm) CMU1202

HIP



Network video Recorder

2MP

Ultra
H.265



Technical Specifications

Model	CMU1202
Camera	
Sensor	1/2.8", 2.0 megapixel, progressive scan, CMOS
Lens	2.8mm@F2.0
Angle of View (H/V)	106.7°, 57.1°
Shutter	Auto/Manual, 1 ~ 1/100000s
Minimum Illumination	Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR on
Day/Night	IR-cut filter with auto switch (ICR)
S/N	>52dB
IR Range/IR	Up to 30m (98ft) IR range
On/Off Control	Auto/Manual
Defog	Digital Defog
WDR	DWDR
Video	
Video Compression	Ultra 265, H.265, H.264
Resolution	Main Stream: 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps Sub Stream: D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CF, Max 30fps; CIF, Max 30fps;
Video Bit Rate	128 Kbps-16 Mbps
Support	Motion Detection, Privacy Mask
Image	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital noise reduction	2D/3D DNR
Flip	Normal/Vertical/Horizontal/180°
HLC	Supported
BLC	Supported
Network	
Protocols	IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP, HTTP
Web Browser	Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+
Network	10/100M Base-TX Ethernet
General	
Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 5.5W
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Ingress Protection	IP67



HIPGROUP



@HIPGROUP



HP Channel



www.hip.co.th

Copyright © HIP GLOBAL. All rights reserved.