

HIP



สัญญาณภาพคมชัด ปลอดภัยทุกพื้นที่

2MP Dual Light Bullet Network Camera (2.8mm)



MODEL
CMU1252

ตอบโจทย์ CCTV HIP คุณภาพ
ภาพคมชัดระดับ Full HD

2.0
MegaPixel

Full HD
CAMERA




Office



Data Room



Apartment



Hotel



Cashbox
Management



Custom



Villa



Bank



2MP



Dual Light



WDR



Built-in Mic



Edge
Storage



Corridor
Mode



POE



IP 67

FEATURES

- ▶ High quality image with 2MP, 1/2.8" CMOS sensor
- ▶ 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
- ▶ Ultra 265, H.265, H.264
- ▶ 120dB true WDR technology enables clear image in strong light scene
- ▶ Support 9:16 Corridor Mode
- ▶ Built-in Mic & Speaker
- ▶ Smart IR, up to 30m (98ft) IR distance
- ▶ White Light, up to 30m (98ft) white light distance
- ▶ Supports 128 G Micro SD card
- ▶ IP67 protection
- ▶ Support PoE power supply
- ▶ 3-Axis

ISO9001:2015

ขอสงวนสิทธิ์ในการเปลี่ยนแปลงรายละเอียดโดยไม่ต้องแจ้งให้ทราบล่วงหน้า บริษัท เอช ไอ พี โกลบอล จำกัด

THE BEST
SECURITY SOLUTION



2MP Dual Light Bullet Network Camera (2.8 mm)

CMU1252



HIP



ใช้งานร่วมกับ Network video Record

Technical Specifications

Model	CMU1252
Camera	
Sensor	1/2.8", 2.0 megapixel, progressive scan, CMOS
Lens	2.8mm@F1.6
Angle of View (H,V)	106.7°, 57.1°
Shutter	Auto/Manual, 1 ~ 1/100000s
Minimum Illumination	Colour: 0.002Lux (F1.6, AGC ON) 0Lux with IR on
Day/Night	IR-cut filter with auto switch (ICR)
S/N	>52dB
IR Range	Up to 30m (98ft) IR range
IR On/Off Control	Auto/Manual
Defog	Digital Defog
WDR	DWDR
Video	
Video Compression	Ultra 265, H.265, H.264
Resolution	Main Stream: 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps Sub Stream: D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF, Max 30fps; CIF, Max 30fps;
Video Bit Rate Support	128 Kbps~6 Mbps Motion Detection , Privacy Mask
Image	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital noise reduction	2D/3D DNR
Flip	Normal/Vertical/Horizontal/180°
HLC	Supported
BLC	Supported
Audio	
Audio Compression	G.711
Two-way Audio	Supported
Suppression	Supported
Sampling Rate	8KHZ
Storage	
Edge Storage	Micro SD, up to 128GB
Network Storage	ANR, NAS(NFS)
Smart	
Behavior Detection	Cross line, intrusion(based on human body detection) motion detection, tampering alarm, audio detection
General Function	Watermark, IP address filtering, access policy, ARP protection, RTSP authentication, user authentication, HTTP authentication
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, SNMP, ONVIF
Web Browser	Plug-in free live view: Chrome57.0+, Firefox 58.0+, Edge 16+
Interface	
Network	10/100M Base-TX Ethernet
Built-in Mic	Supported
Built-in Speaker	Supported
General	
Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 9.0W
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Ingress Protection	IP67

